

# Multi-Housing

## FULL LINE CATALOG



WHAT'S INSIDE MATTERS™







## FAMOUSLY DEPENDABLE. NOTORIOUSLY COST-EFFICIENT.

---

Almost nowhere is dependability more critical than to a multi-housing laundry facility, where meeting the cleaning expectations of a diverse group of individuals—as well as your need for durability—can be challenging.

That's why at Maytag® Commercial Laundry, dependability has never been just a word. It's a mission. A commitment we make to you, and your customers, and a feature we build into every door, drum and drive shaft inside every machine we design. It's also a reputation we at Maytag have spent more than a century building, and re-earning, day after day. How? By consistently designing, innovating and delivering the hardest working and longest lasting laundry equipment in the industry. Including pioneering significant advances in energy efficiency, and offering more energy-saving solutions than any other brand.

Then there's our extensive network of expert distributors, on whom you can depend for assistance with everything from machine selection to installation, laundry room planning to renovation, and space efficiency to cost efficiency—whatever the location or size of the laundry room. As well as route operators to keep you up and running, and your residents happy. No wonder customers trust Maytag® Commercial Laundry to protect what they put inside, and have made our famously dependable machines America's #1 preferred laundry brand.\*

\*Based on current 12-Approved Consumer State Tracker, 2010 Smith Dahmer Associates, LLC.

## Maytag® Energy Advantage™ High-Efficiency Lineup of Washers and Dryers

### CUT UTILITY COSTS. DRAMATICALLY. NOT CLEANING POWER.

Save up to 60%\* with ENERGY ADVANTAGE™ washers and dryers.

When you put Maytag® Energy Advantage™ equipment in your laundry facilities, you and your residents get more than a premium amenity. You get decreased cycle times. Shorter drying times. More durable machines. And more energy-saving options than any other brand to help cut utility costs up to 60%\*. But that's just the beginning. Ever



since Maytag built the first appliance ever to receive the ENERGY STAR® label, we've continued providing energy-saving solutions, including our highly efficient ENERGY STAR®-qualified washers.

Some models are also CEE Tier III rated for the highest level of energy and water efficiency.

You'll find that our single-load, high-efficiency washers clean better than any other washers in their class. Add programmable features to further increase revenue, and the convenience and added security of coinless card payment options, and there's no question this high-efficiency series could be the best thing that ever happened to your bottom line.

### KEEP AN EYE ON YOUR INVESTMENT... FROM ANYWHERE.

Introducing Maytag Connect 360™



It's just one more way to reduce downtime, increase profits and efficiency, and make lives simpler: yours and your residents. Introducing Maytag Connect 360™—our new fully wireless web-based tracking technology.

Imagine: Now you can receive instant notification the moment a machine is out of order, and that same message will be forwarded to a service tech instantaneously, with the specific error code. Or residents can receive a text automatically, the second their cycle is complete. Those are just a few of the ways this innovative new technology is going to revolutionize the laundry room, and drive your profits sky high. All as fast as you can hit "send" and "receive."

Now that's Maytag in action for you!

\*Maytag Commercial front-load washer compared to commercial top-load washer.  
Based on American Home Appliance Manufacturers (AHAM) load sizes. Individual savings may vary.





## MAYTAG® COMMERCIAL ENERGY ADVANTAGE™ HIGH-EFFICIENCY FRONT-LOAD WASHERS

Modified Energy Factor: 2.49

Water Factor: 3.7

CEE Tier III Rated



MHN30PDB



MHN30PRB  
MHN30PNB Export model only

### MAYTAG® COMMERCIAL ENERGY ADVANTAGE™ HIGH-EFFICIENCY FRONT-LOAD WASHERS

- Save up to 60% yearly on water, energy and sewer costs.\*
- High-efficiency design meets CEE Tier III rating.
- TurboWash™ System delivers better cleaning with less average water use per cycle.
- Super Cycle option increases revenue.
- Self-diagnostic feature cuts service cost and minimizes downtime.
- High-speed extraction cuts drying time.
- Porcelain-enamel top with backsplash.
- Maytag Connect 360™ wireless audit system.
- Precision endurance drive.
- Controlled induction motor.
- High-security vault.
- Large 3.1-cu.-ft. capacity for bulky items.

\*Maytag® Commercial front-load washer compared to commercial top-load washer. Individual savings may vary.

**Use this key to determine the payment option type specified in each model number:**

PD = Microprocessor Coin-Drop | PR = Microprocessor Card Reader-Ready | CS = Mechanical Coin Slide-Ready | PN = Microprocessor Non-Coin

# HIGH-EFFICIENCY FRONT-LOAD WASHERS

| WASHER SPECIFICATIONS                                                              |                 |                      |
|------------------------------------------------------------------------------------|-----------------|----------------------|
| MODEL                                                                              | MHN30PDB        | MHN30PRB             |
| EXPORT MODEL                                                                       |                 | MHN30PNB             |
| PAYMENT OPTION TYPE                                                                | Coin-Drop       | Card Reader/Non-Coin |
| MOTOR                                                                              |                 |                      |
| Variable-speed, reversible, thermoprotected, high-efficiency, controlled induction | ✓               | ✓                    |
| Wash—HP (kw)                                                                       | .09 (.07)       | .09 (.07)            |
| Extract—HP (kw)                                                                    | .54 (40)        | .54 (40)             |
| Average energy consumption per cycle (kWh)                                         | .054            | .054                 |
| APPROXIMATE WATER USAGE—GALLONS (LITERS)                                           |                 |                      |
| Average hot water usage, hot water cycle                                           | 3.4 (12.8)      | 3.4 (12.8)           |
| Average hot water usage, warm water cycle                                          | 1.6 (6.1)       | 1.6 (6.1)            |
| Average total water usage per cycle                                                | 11.5 (43)*      | 11.5 (43)*           |
| ELECTRIC RATING                                                                    |                 |                      |
| Domestic model—voltage/Hz                                                          | 120/60          | 120/60               |
| Export model—voltage/Hz                                                            | 220–240/50      | 220–240/50           |
| BREAKER/FUSE MINIMUM REQUIREMENTS                                                  |                 |                      |
| Domestic model—amps                                                                | 15              | 15                   |
| Export model—amps                                                                  | 10              | 10                   |
| CAPACITY                                                                           |                 |                      |
| Cylinder volume—cu. ft. (liters)                                                   | 3.1 (88)        | 3.1 (88)             |
| Cylinder diameter—in. (mm)                                                         | 21.6 (549)      | 21.6 (549)           |
| Cylinder depth—in. (mm)                                                            | 13.4 (340)      | 13.4 (340)           |
| SOUND LEVEL (EXPORT MODEL ONLY)                                                    |                 |                      |
| Sound pressure level, Lpa (dBA) (Kpa: ± 3.6 dBA)                                   | 58              | 58                   |
| WASH SPEED                                                                         |                 |                      |
| RPM                                                                                | 40              | 40                   |
| EXTRACT SPEED                                                                      |                 |                      |
| Maximum RPM                                                                        | 1,000           | 1,000                |
| Maximum G-Force                                                                    | 306             | 306                  |
| OPERATING PRESSURE                                                                 |                 |                      |
| Psi (bar)                                                                          | 20–100 (1–8)    | 20–100 (1–8)         |
| INLET HOSE LENGTH                                                                  |                 |                      |
| Ft. (m)                                                                            | 4 (1.22)        | 4 (1.22)             |
| DRAIN HOSE LENGTH                                                                  |                 |                      |
| Ft. (m)                                                                            | 6 (1.83)        | 6 (1.83)             |
| ADJUSTABLE LEVELING LEGS                                                           |                 |                      |
|                                                                                    | ✓               | ✓                    |
| APPROXIMATE WEIGHT                                                                 |                 |                      |
| Crated—lbs. (kg)                                                                   | 254 (115)       | 244 (111)            |
| Uncrated—lbs. (kg)                                                                 | 245 (111)       | 235 (107)            |
| DIMENSIONS                                                                         |                 |                      |
| Height—in. (mm)                                                                    | 45.67 (1,160)** | 38.94 (983)          |
| Width—in. (mm)                                                                     | 27 (686)        | 27 (686)             |
| Depth—in. (mm)                                                                     | 29.25 (743)     | 29.25 (743)          |
| Door opening—sq. in.                                                               | 143             | 143                  |

\*Average based on DOE J1 testing with factory preset cycles.

\*\*Height at metercase top does not include pedestal.

Dimensions are for planning purposes only. See specific instructions for proper installation. Because of continuous product improvement, Maytag reserves the right to change specifications without notice. Export model ships without coin-drop mechanism.

## MAYTAG® COMMERCIAL ENERGY ADVANTAGE™ TOP-LOAD WASHERS

Our most energy-efficient top-load washer equipped with customizable wash cycles for maximum performance.



MVW18PD



MVW18PR



MVW18CS

### **MAYTAG® COMMERCIAL ENERGY ADVANTAGE™ TOP-LOAD WASHERS WITH MICROPROCESSOR CONTROLS**

- Sensor fill water levels reduce water usage.
- Our most energy-efficient top-load washer.
- High-speed spin of 144 G-Force reduces dry time.
- User-friendly controls allow for customized cleaning.
- Front access for easier self-service.
- Premium porcelain-enamel top.
- Microprocessor controls for ultimate cycle selection.
- Smooth balance suspension system.
- Maytag Connect 360™ wireless audit system.
- Displays vend price and cycle time remaining.
- Multiple revenue generating options.

### **MAYTAG® COMMERCIAL ENERGY ADVANTAGE™ TOP-LOAD WASHER WITH MICROPROCESSOR CONTROLS**

- Sensor fill water levels reduce water usage.
- Our most energy-efficient top-load washer.
- High-speed spin of 144 G-Force reduces dry time.
- Multiple revenue generating options.
- Easy-to-operate manual controls.
- Front access for easier self-service.
- Clothes guard keeps laundry from pump.
- Premium porcelain-enamel top.
- Microprocessor controls for ultimate cycle selection.
- Smooth balance suspension system.
- Displays vend price and cycle time remaining.

# TOP-LOAD WASHERS

| WASHER SPECIFICATIONS                                  |              |                |              |
|--------------------------------------------------------|--------------|----------------|--------------|
| MODEL                                                  | MVW18PD      | MVW18PR        | MVW18CS      |
| PAYMENT OPTION TYPE                                    | Coin-Drop    | Card Reader    | Coin Slide   |
| MOTOR                                                  |              |                |              |
| Single-phase, reversible, thermoprotected, high torque | ✓            | ✓              | ✓            |
| HP (kw)                                                | .33 (.25)    | .33 (.25)      | .33 (.25)    |
| APPROXIMATE WATER USAGE—GALLONS (LITERS)               |              |                |              |
| Average hot water usage, hot water cycle               | 6.1 (22.9)*  | 6.1 (22.9)*    | 6.1 (22.9)*  |
| Average hot water usage, warm water cycle              | —            | —              | —            |
| Average total water usage per cycle                    | 19.9 (75)*   | 19.9 (75)*     | 19.9 (75)*   |
| ELECTRIC RATING                                        |              |                |              |
| Domestic model—voltage/Hz                              | 120/60       | 120/60         | 120/60       |
| Export model—voltage/Hz                                | 220–240/50   | —              | 220–240/50   |
| BREAKER/FUSE MINIMUM REQUIREMENTS                      |              |                |              |
| Domestic model—amps                                    | 15           | 15             | 15           |
| Export model—amps                                      | 10           | —              | 10           |
| CAPACITY                                               |              |                |              |
| Cylinder volume—cu. ft. (liters)                       | 2.9 (82)     | 2.9 (82)       | 2.9 (82)     |
| Cylinder diameter—in. (mm)                             | 20.8 (528)   | 20.8 (528)     | 20.8 (528)   |
| Cylinder depth—in. (mm)                                | 23.8 (605)   | 23.8 (605)     | 23.8 (605)   |
| EXTRACT SPEED                                          |              |                |              |
| Maximum RPM                                            | 700          | 700            | 700          |
| Maximum G-Force                                        | 144          | 144            | 144          |
| OPERATING PRESSURE                                     |              |                |              |
| Psi (bar)                                              | 20–100 (1–8) | 20–100 (1–8)   | 20–100 (1–8) |
| INLET HOSE LENGTH                                      |              |                |              |
| Ft. (m)                                                | 6 (1.8)      | 6 (1.8)        | 6 (1.8)      |
| DRAIN HOSE LENGTH                                      |              |                |              |
| Ft. (m)                                                | 4.2 (1.3)    | 4.2 (1.3)      | 4.2 (1.3)    |
| ADJUSTABLE LEVELING LEGS                               | ✓            | ✓              | ✓            |
| APPROXIMATE WEIGHT                                     |              |                |              |
| Crated—lbs. (kg)                                       | 152 (69)     | 140 (64)       | 148 (67)     |
| Uncrated—lbs. (kg)                                     | 136 (62)     | 125 (57)       | 132 (60)     |
| DIMENSIONS                                             |              |                |              |
| Height—in. (mm)                                        | 43 (1,092)** | 40.8 (1,037)** | 43 (1,092)** |
| Width—in. (mm)                                         | 27 (686)     | 27 (686)       | 27 (686)     |
| Depth—in. (mm)                                         | 25.9 (658)   | 25.9 (658)     | 25.9 (658)   |
| Lid opening—in. (mm)                                   | 17 (432)     | 17 (432)       | 17 (432)     |

\*Average based on DOE J1 testing with factory preset cycles.

\*\*Height at metercase top does not include pedestal.

Dimensions are for planning purposes only. See specific instructions for proper installation. Because of continuous product improvement, Maytag reserves the right to change specifications without notice.

Export model ships without coin-drop mechanism.

## MAYTAG® COMMERCIAL SUPER-CAPACITY SINGLE-LOAD DRYERS



MDE/MDG25PD



MDE/MDG25PR  
MDE/MDG25PN Export model only

### MAYTAG® COMMERCIAL SUPER-CAPACITY DRYERS

- TurboVent™ Technology provides faster drying and better performance on long vents.
- Advanced Computer Trac® controls allow for easy programming.
- Front access for easier self-service.
- Maytag Connect 360°™ wireless audit system.
- Card reader-compatible.
- Porcelain-enamel top with backsplash.
- Four-roller suspension with permanently lubricated bearings.
- Blower guard reduces service calls.
- High-security vault.
- Extra-large 6.7-cu.-ft. capacity.
- Easy-to-use, one-touch cycle selection.

# SUPER-CAPACITY SINGLE-LOAD DRYERS

| DRYER SPECIFICATIONS                                       |                   |                      |
|------------------------------------------------------------|-------------------|----------------------|
| MODEL                                                      | MDE/MDG25PD       | MDE/MDG25PR          |
| EXPORT MODEL                                               |                   | MDE/MDG25PN          |
| PAYMENT OPTION TYPE                                        | Coin-Drop         | Card Reader/Non-Coin |
| MOTOR                                                      |                   |                      |
| Single-phase, thermoprotected against overload, auto-reset | ✓                 | ✓                    |
| HP (kw)                                                    | .33 (.25)         | .33 (.25)            |
| TUMBLE SPEED—RPM                                           | 50 ± 1            | 50 ± 1               |
| CAPACITY                                                   |                   |                      |
| Cu. ft. (liters)                                           | 6.7 (190)         | 6.7 (190)            |
| AIRFLOW                                                    |                   |                      |
| Gas models—cfm (cmm)                                       | 230 (6.5)         | 230 (6.5)            |
| Electric models—cfm (cmm)                                  | 215 (6.1)         | 215 (6.1)            |
| SOUND LEVEL (EXPORT MODEL ONLY)                            |                   |                      |
| Sound pressure level, Lpa (dBA) (Kpa: ± 10 dBA)            | 58                | 58                   |
| ELECTRICAL REQUIREMENTS                                    |                   |                      |
| MDE model—voltage/Hz                                       | 240/60            | 240/60               |
| MDG model—voltage/Hz                                       | 120/60            | 120/60               |
| Export models—voltage/Hz                                   | 220–240/50        | 220–240/50           |
| BREAKER/FUSE MINIMUM REQUIREMENTS                          |                   |                      |
| MDE model—amps                                             | 30                | 30                   |
| MDG model—amps                                             | 15                | 15                   |
| MDE export model—amps                                      | 25                | 25                   |
| MDG export model—amps                                      | 10                | 10                   |
| ELECTRIC HEATING ELEMENT—WATTS                             |                   |                      |
| Domestic models                                            | 5,600             | 5,600                |
| Export models                                              | 4,600             | 4,600                |
| Canadian models                                            | 5,250             | 5,250                |
| GAS RATING                                                 |                   |                      |
| MDG model—BTU/hr. (kcal/hr.)                               | 24,000 (6,048)    | 24,000 (6,048)       |
| MDG export model—BTU/hr. (kcal/hr.)                        | 20,000 (5,040)    | 20,000 (5,040)       |
| GAS INLET                                                  |                   |                      |
| MDG model—in.                                              | 3/8 N.P.T.        | 3/8 N.P.T.           |
| EXHAUST DUCT DIAMETER                                      |                   |                      |
| In. (mm)                                                   | 4 (100)*          | 4 (100)*             |
| ELECTRONIC BURNER IGNITION                                 |                   |                      |
| MDG model                                                  | ✓                 | ✓                    |
| ADJUSTABLE LEVELING LEGS                                   |                   |                      |
|                                                            | ✓                 | ✓                    |
| APPROXIMATE WEIGHT                                         |                   |                      |
| Crated—lbs. (kg) electric/gas                              | 160 (73)/163 (74) | 144 (65)/147 (67)    |
| Uncrated—lbs. (kg) electric/gas                            | 147 (67)/150 (68) | 133 (60)/136 (62)    |
| DIMENSIONS                                                 |                   |                      |
| Height—in. (mm)                                            | 45.75 (1,162)**   | 39.25 (997)          |
| Width—in. (mm)                                             | 27 (686)          | 27 (686)             |
| Depth—in. (mm)                                             | 29 (737)          | 29 (737)             |
| Door opening—sq. in.                                       | 191               | 191                  |

\*Use 4" (100 mm) diameter rigid aluminum or galvanized steel duct. Never use plastic, non-metal or combustible duct.

\*\*Includes height of metercase.

See specific instructions for proper installation. Because of continuous product improvement, Maytag reserves the right to change specifications without notice.  
Export model ships without coin-drop mechanism.

## MAYTAG® COMMERCIAL SUPER-CAPACITY SINGLE-LOAD DRYERS



MDE/MDG18PD



MDE/MDG18PR



MDE/MDG18CS

### MAYTAG® COMMERCIAL SUPER-CAPACITY DRYERS

- TurboVent™ Technology provides faster drying and better performance on long vents.
- 4-way venting—right or left side, back or front.
- Advanced Computer Trac® controls allow for easy programming.
- Coin slide model accepts a variety of slides.
- Front access for easier self-service.
- Maytag Connect 360™ wireless audit system—PD and PR models.
- Premium porcelain-enamel top.
- Four-roller suspension with permanently lubricated bearings.
- Blower guard reduces service calls.
- High-security vault.
- Extra large 7.4-cu.-ft. capacity.

# SUPER-CAPACITY SINGLE-LOAD DRYERS

| DRYER SPECIFICATIONS                                       |                  |                |                  |
|------------------------------------------------------------|------------------|----------------|------------------|
| MODEL                                                      | MDE/MDG18PD      | MDE/MDG18PR    | MDE/MDG18CS      |
| PAYMENT OPTION TYPE                                        | Coin-Drop        | Card Reader    | Coin Slide       |
| MOTOR                                                      |                  |                |                  |
| Single-phase, thermoprotected against overload, auto-reset | ✓                | ✓              | ✓                |
| HP (kw)                                                    | .33 (.25)        | .33 (.25)      | .33 (.25)        |
| TUMBLE SPEED—RPM                                           | 50 ± 1           | 50 ± 1         | 50 ± 1           |
| CAPACITY                                                   |                  |                |                  |
| Cu. ft. (liters)                                           | 7.4 (210)        | 7.4 (210)      | 7.4 (210)        |
| AIRFLOW                                                    |                  |                |                  |
| Gas models—cfm (cmm)                                       | 230 (6.5)        | 230 (6.5)      | 230 (6.5)        |
| Electric models—cfm (cmm)                                  | 215 (6.1)        | 215 (6.1)      | 215 (6.1)        |
| SOUND LEVEL (EXPORT MODEL ONLY)                            |                  |                |                  |
| Sound pressure level, Lpa (dBA) (Kpa: ± 10dBA)             | —                | —              | 58               |
| ELECTRICAL REQUIREMENTS                                    |                  |                |                  |
| MDE model—voltage/Hz                                       | 240/60*          | 240/60*        | 240/60*          |
| MDG model—voltage/Hz                                       | 120/60           | 120/60         | 120/60           |
| Export models—voltage/Hz                                   | 220–240/50       | —              | 220–240/50       |
| BREAKER/FUSE MINIMUM REQUIREMENTS                          |                  |                |                  |
| MDE model—amps                                             | 30               | 30             | 30               |
| MDG model—amps                                             | 15               | 15             | 15               |
| MDE export model—amps                                      | 25               | —              | 25               |
| MDG export model—amps                                      | 10               | —              | 10               |
| ELECTRIC HEATING ELEMENT—WATTS                             |                  |                |                  |
| Domestic models                                            | 5,600            | 5,600          | 5,600            |
| Export models                                              | 4,600            | —              | 4,600            |
| Canadian models                                            | 5,250            | 5,250          | 5,250            |
| GAS RATING                                                 |                  |                |                  |
| MDG model—BTU/hr. (kcal/hr.)                               | 24,000 (6,048)   | 24,000 (6,048) | 24,000 (6,048)   |
| MDG export model—BTU/hr. (kcal/hr.)                        | 20,000 (5,040)   | —              | 20,000 (5,040)   |
| GAS INLET                                                  |                  |                |                  |
| MDG model—in.                                              | 3/8 N.P.T.       | 3/8 N.P.T.     | 3/8 N.P.T.       |
| EXHAUST DUCT DIAMETER                                      |                  |                |                  |
| In. (mm)                                                   | 4 (101.6)**      | 4 (101.6)**    | 4 (101.6)**      |
| ELECTRONIC BURNER IGNITION                                 |                  |                |                  |
| MDG models                                                 | ✓                | ✓              | ✓                |
| AUTOMATIC PRESSURE REGULATOR                               |                  |                |                  |
| MDG models                                                 | ✓                | ✓              | ✓                |
| ADJUSTABLE LEVELING LEGS                                   | ✓                | ✓              | ✓                |
| APPROXIMATE WEIGHT                                         |                  |                |                  |
| Crated—lbs. (kg)                                           | 154 (69.8)       | 140 (63.5)     | 154 (69.8)       |
| Uncrated—lbs. (kg)                                         | 140 (63.5)       | 126 (57.2)     | 140 (63.5)       |
| DIMENSIONS                                                 |                  |                |                  |
| Height—in. (mm)                                            | 43.25 (1,099)*** | 41 (1,040)***  | 43.25 (1,099)*** |
| Width—in. (mm)                                             | 27 (686)         | 27 (686)       | 27 (686)         |
| Depth—in. (mm)                                             | 29.25 (743)      | 29.25 (743)    | 29.25 (743)      |

\*208-Volt electric element kit available.

\*\*Use 4" (106 mm) diameter rigid aluminum or galvanized steel duct. Never use plastic, non-metal or combustible duct.

\*\*\*Height at top of metercase.

See specific instructions for proper installation. Because of continuous product improvement, Maytag reserves the right to change specifications without notice.

## MAYTAG® COMMERCIAL SUPER-CAPACITY SINGLE-LOAD STACK DRYERS

With our single-load stack dryers, you'll fit two drying pockets in the floor space of just one.



MLE/MLG24PD



MLE/MLG24PR  
MLE/MLG24PN Export model only

### MAYTAG® COMMERCIAL SINGLE-LOAD SUPER-CAPACITY STACK DRYERS

- TurboVent™ Technology provides faster drying and better performance on long vents.
- Advanced Computer Trac® controls allow for easy programming.
- Front access for easier self-service.
- Maytag Connect 360™ wireless audit system.
- Debit card compatibility.
- Four-roller suspension with permanently lubricated bearings.
- Blower guard reduces service calls.
- Extra-large 7.4-cu.-ft. capacity.
- Easy-to-use, one-touch cycle selection.
- High airflow for better clothing care.

# SUPER-CAPACITY SINGLE-LOAD STACK DRYERS

| DRYER SPECIFICATIONS                                       |                           |                      |
|------------------------------------------------------------|---------------------------|----------------------|
| MODEL                                                      | MLE/MLG24PD               | MLE/MLG24PR          |
| EXPORT MODEL                                               |                           | MLE/MLG24PN          |
| PAYMENT OPTION TYPE                                        | Coin-Drop/Card Compatible | Card Reader/Non-Coin |
| MOTOR                                                      |                           |                      |
| Single-phase, thermoprotected against overload, auto-reset | ✓                         | ✓                    |
| HP (kw)                                                    | .33 (.25)                 | .33 (.25)            |
| TUMBLE SPEED—RPM                                           | 50 ± 1                    | 50 ± 1               |
| CAPACITY                                                   |                           |                      |
| Cu. ft. (liters)                                           | 7.4 (209.5)               | 7.4 (209.5)          |
| AIRFLOW—CFM (CMM)                                          |                           |                      |
| Gas/electric models—per pocket                             | 230 (6.5)/215 (6.1)       | 230 (6.5)/215 (6.1)  |
| Export, gas/electric models—per pocket                     | 230 (6.5)/215 (6.1)       | 230 (6.5)/215 (6.1)  |
| SOUND LEVEL (EXPORT MODEL ONLY)                            |                           |                      |
| Sound pressure level, Lpa (dBA) (Kpa: ± 10 dBA)            | 58                        | 58                   |
| ELECTRICAL REQUIREMENTS                                    |                           |                      |
| MLE model—voltage/Hz                                       | 240/60*                   | 240/60*              |
| MLG model—voltage/Hz                                       | 120/60                    | 120/60               |
| Export models—voltage/Hz                                   | 220–240/50                | 220–240/50           |
| BREAKER/FUSE MINIMUM REQUIREMENTS—AMPS                     |                           |                      |
| MLE electric model—domestic (each drying chamber)          | 30                        | 30                   |
| MLE electric model—export (one terminal block per stack)   | 50                        | 50                   |
| MLE electric model—Canada (one terminal block per stack)   | 60                        | 60                   |
| MLG gas models, all versions—(each drying chamber)         | 15                        | 15                   |
| MLG export model—(one terminal block per stack)            | 15                        | 15                   |
| HEATER ELEMENT RATING—WATTS                                |                           |                      |
| Domestic model—per pocket                                  | 5,600                     | 5,600                |
| Export models—per pocket                                   | 4,600                     | 4,600                |
| Canadian models                                            | 5,250                     | 5,250                |
| GAS RATING                                                 |                           |                      |
| MLG models—BTU/hr. (kcal/hr.)                              | 24,000 (6,048)            | 24,000 (6,048)       |
| MLG export model—BTU/hr. (kcal/hr.)                        | 20,000 (5,040)            | 20,000 (5,040)       |
| GAS INLET                                                  |                           |                      |
| MLG models—in.                                             | 3/8 N.P.T.                | 3/8 N.P.T.           |
| EXHAUST DUCT DIAMETER                                      |                           |                      |
| In. (mm)                                                   | 4 (101.6)**               | 4 (101.6)**          |
| ELECTRONIC BURNER IGNITION                                 |                           |                      |
| MLG models                                                 | ✓                         | ✓                    |
| AUTOMATIC PRESSURE REGULATOR                               |                           |                      |
| MLG models                                                 | ✓                         | ✓                    |
| ADJUSTABLE LEVELING LEGS                                   | ✓                         | ✓                    |
| APPROXIMATE WEIGHT                                         |                           |                      |
| Crated—lbs. (kg) electric/gas                              | 290 (131.5)               | 275 (124.7)          |
| Uncrated—lbs. (kg) electric/gas                            | 265 (120.2)               | 250 (113.4)          |
| DIMENSIONS                                                 |                           |                      |
| Height—in. (mm)                                            | 76.75 (1,949)             | 76.75 (1,949)        |
| Width—in. (mm)                                             | 27 (686)                  | 27 (686)             |
| Depth—in. (mm)                                             | 29 (737)                  | 29 (737)             |

\*208-Volt electrical element kit available.

\*\*Use 4" (100 mm) diameter rigid aluminum or galvanized steel duct. Never use plastic, non-metal or combustible duct.

See specific instructions for proper installation. Because of continuous product improvement, Maytag reserves the right to change specifications without notice.

## MAYTAG® COMMERCIAL ENERGY ADVANTAGE™ STACK WASHER/DRYERS

Modified Energy Factor: 2.49

Water Factor: 3.7

CEE Tier III Rated



MLE/MLG20PDB



MLE/MLG20PRB  
MLE/MLG20PNB Export model only

### MAYTAG® COMMERCIAL ENERGY ADVANTAGE™ STACK WASHER/DRYERS

- Save up to 60% yearly on water, energy and sewer costs.\*
- High-efficiency washer meets CEE Tier III rating.
- Super Cycle option increases revenue.
- Maytag Connect 360™ wireless audit system.
- Card reader-compatible.
- Precision endurance drive.
- Single payment system.
- Large capacity for bulky items—3.1-cu.-ft. capacity washer/6.7-cu.-ft. capacity dryer.
- High-speed extraction cuts drying time (as high as 1,000 RPMs).
- 180° door opening with heavy-duty die-cast hinge, washer only.

\*Maytag® Commercial front-load washer compared to commercial top-load washer. Individual savings may vary.

## STACK WASHER/DRYERS

| WASHER SPECIFICATIONS                                                                           |                           |                      |
|-------------------------------------------------------------------------------------------------|---------------------------|----------------------|
| MODEL                                                                                           | MLE/MLG20PDB              | MLE/MLG20PRB         |
| EXPORT MODEL                                                                                    |                           | MLE/MLG20PNB         |
| PAYMENT OPTION TYPE                                                                             | Coin-Drop/Card Compatible | Card Reader/Non-Coin |
| MOTOR                                                                                           |                           |                      |
| 120V, 60 Hz, variable-speed, reversible, thermoprotected, high-efficiency, controlled induction | ✓                         | ✓                    |
| Export models—220–240V, 50Hz                                                                    | ✓                         | ✓                    |
| Wash—HP (kw)                                                                                    | .09 (.07)                 | .09 (.07)            |
| Extract—HP (kw)                                                                                 | .54 (40)                  | .54 (40)             |
| Average energy consumption per cycle (kWh)                                                      | .054                      | .054                 |
| APPROXIMATE WATER USAGE—GALLONS (LITERS)                                                        |                           |                      |
| Average hot water usage, hot water cycle                                                        | 3.4 (12.8)                | 3.4 (12.8)           |
| Average hot water usage, warm water cycle                                                       | 1.6 (6.1)                 | 1.6 (6.1)            |
| Average total water usage per cycle                                                             | 11.5 (43)*                | 11.5 (43)*           |
| SPEED                                                                                           |                           |                      |
| Wash speed—RPM                                                                                  | 40                        | 40                   |
| Extract speed—max RPM/max G-Force                                                               | 1,000/306                 | 1,000/306            |
| BREAKER/FUSE MINIMUM REQUIREMENTS                                                               |                           |                      |
| MLE electric models—amps/MLE export electric—amps                                               | 30/40                     | 30/40                |
| MLE Canadian electric models—amps                                                               | 40                        | 40                   |
| MLG gas model/export gas model—amps                                                             | 15/10                     | 15/10                |
| CAPACITY                                                                                        |                           |                      |
| Cylinder volume—cu. ft. (liters)                                                                | 3.1 (88)                  | 3.1 (88)             |
| Cylinder diameter—in. (mm)                                                                      | 21.6 (549)                | 21.6 (549)           |
| Cylinder depth—in. (mm)                                                                         | 13.4 (340)                | 13.4 (340)           |
| SOUND LEVEL (EXPORT MODEL ONLY)                                                                 |                           |                      |
| Sound pressure level, Lpa (dBA) (Kpa: ± 3.6 dBA)                                                | 58                        | 58                   |
| WATER INLET/HOSE                                                                                |                           |                      |
| Inlet hose length/drain hose length—ft. (m)                                                     | 4 (1.22)/6 (1.83)         | 4 (1.22)/6 (1.83)    |
| Water supply pressure—psi (bar)                                                                 | 20–100 (1–8)              | 20–100 (1–8)         |
| DRYER SPECIFICATIONS                                                                            |                           |                      |
| MOTOR                                                                                           |                           |                      |
| Variable-speed, reversible, thermoprotected, high-efficiency, controlled induction              | ✓                         | ✓                    |
| HP (kw)                                                                                         | .33 (.25)                 | .33 (.25)            |
| Tumble speed—RPM                                                                                | 50 ± 1                    | 50 ± 1               |
| CAPACITY—CU. FT. (LITERS)                                                                       |                           |                      |
|                                                                                                 | 6.7 (190)                 | 6.7 (190)            |
| AIRFLOW                                                                                         |                           |                      |
| MLG gas models—cfm (cmm)                                                                        | 230 (6.5)                 | 230 (6.5)            |
| MLE electric models—cfm (cmm)                                                                   | 215 (6.1)                 | 215 (6.1)            |
| ELECTRICAL REQUIREMENTS—VOLTS/HZ                                                                |                           |                      |
| MLE electric model—MLG gas model                                                                | 240/60–120/60             | 240/60–120/60        |
| Export models                                                                                   | 220–240/50                | 220–240/50           |
| HEATER ELEMENT RATING                                                                           |                           |                      |
| MLE electric domestic models/export models—watts                                                | 5,600/4,600               | 5,600/4,600          |
| MLE electric Canadian models—watts                                                              | 5,250                     | 5,250                |
| MLG gas domestic models—BTU/hr. (kcal/hr.)                                                      | 24,000 (6,048)            | 24,000 (6,048)       |
| MLG gas export models—BTU/hr. (kcal/hr.)                                                        | 20,000 (5,040)            | 20,000 (5,040)       |
| GAS INLET                                                                                       |                           |                      |
| MLG model—in.                                                                                   | 3/8 N.P.T.                | 3/8 N.P.T.           |
| ADJUSTABLE LEVELING LEGS                                                                        |                           |                      |
|                                                                                                 | ✓                         | ✓                    |
| COLOR                                                                                           |                           |                      |
|                                                                                                 | White                     | White                |
| APPROXIMATE WEIGHT                                                                              |                           |                      |
| Crated—lbs. (kg) electric/gas                                                                   | 383 (173)/389 (176)       | 369 (167)            |
| Uncrated—lbs. (kg) electric/gas                                                                 | 372 (169)/378 (171)       | 358 (162)            |
| DIMENSIONS                                                                                      |                           |                      |
| Product height—in. (mm)                                                                         | 74 (1,880)                | 74 (1,880)           |
| Width—in. (mm)                                                                                  | 27 (686)                  | 27 (686)             |
| Depth—in. (mm)                                                                                  | 29.5 (749)                | 29.5 (749)           |
| Door opening—washer—sq. in.                                                                     | 143                       | 143                  |
| Door opening—dryer—sq. in.                                                                      | 191                       | 191                  |

\*Average based on DOE J1 testing with factory preset cycles.  
Because of continuous product improvement, Maytag reserves the right to change specifications without notice.


## THREE PAYMENT OPTIONS. THE CHOICE IS YOURS.

---


Most Maytag® Commercial Laundry equipment comes equipped to accept multiple payment options—from coin-drop to coin slide to a variety of card payment systems.

Perfect for colleges and universities, card payment systems make “change” a thing of the past, and provide added security and reduce vandalism since there are never any coins in the machines.

To prevent slugging, coin-drop models feature an optical sensor that measures the size, weight and drop speed of a coin before it's accepted. And, our coin slide models are equipped to accept a variety of slides.



Coin-Drop



Coin Slide



Card Reader-Ready







**WHAT'S INSIDE MATTERS™**

[www.maytagcommerciallaundry.com](http://www.maytagcommerciallaundry.com)

1-800-662-3587

To download a digital version of this brochure,  
[visit mclaundry.com](http://visit mclaundry.com)

